HUB

HUB RESEARCH PAPER

The application of PHstat leaching tests
to assess the PH-dependent release
of trace metals from soils, sediments
and waste materials

Valérie Cappuyns and Rudy Swennen

Centrum voor Duurzaam Ondernemen

HUB RESEARCH PAPER 2007/22.
SEPTEMBER 2007

Hogeschool - Universiteit Brussel

Stormstraat 2, 1000 Brussel, Belgium
T: +32 2 210 12 11 F: + 32 2 217 64 64

THE APPLICATION OF pH_{STAT} LEACHING TESTS TO ASSESS THE PH-DEPENDENT RELEASE OF TRACE METALS FROM SOILS, SEDIMENTS AND WASTE MATERIALS

Valérie Cappuyns^{1,2}, Rudy Swennen²

¹European University College Brussels, Centre for Corporate Sustainability, Stormstraat 2, 1000 Brussels, BELGIUM. Tel: +3222101675, Fax: +3222101619, e-mail: valerie.cappuyns@ehsal.be

²Katholieke Universiteit Leuven, Geology, Celestijnenlaan 200 E, 3001 Heverlee, Belgium, Tel: +3216327297; e-mail: Rudy.Swennen@geo.kuleuven.be

Key words: contamination, acid neutralizing capacity, acidification, leaching, pH, soil, titration, trace metals

Abbreviations: ANC = acid neutralizing capacity, BNC = base neutralizing capacity, CEC = cation exchange capacity, DOC = dissolved organic carbon, DIC = dissolved inorganic carbon, EC = electrical conductivity, L/S = Liquid/Solid ratio, RC = release capacity, XRD = X-ray diffraction

Abstract

pH is one of the key parameters that determines heavy metal mobility in soils, sediments and waste materials. In many respects leaching behaviour as reflected by the pH_{stat} leaching tests provide a better means of assessing environmental impact than analysis of total elemental composition. This paper discusses the use of pH_{stat} leaching tests as a tool to assess the potential mobilisation of trace metals from soils, sediments and waste materials. The possibilities of pH_{stat} leaching tests are illustrated by means of different examples.

Titration curves (ANC=acid neutralizing capacity) obtained in the pH_{stat} tests with continuous setpoint titration and the release of elements as a function of time were described as the sum of two independent first-order reactions, which represent 'buffers' or 'pools' with a different reactivity.

The mathematical description of metal leaching behaviour from soils and sediments enabled a distinction between 5 groups of elements with a different leaching behaviour, which could be related to 'pools' with different reactivity. Contrary to single and sequential extractions, where attention is focussed on the reactivity towards a *reagent* (which is often difficult to link with a natural process), the reactivity and mobility of metals as a consequence of a *process* (acidification in the case of pH_{stat} leaching) is investigated. Moreover, the potential buffering capacity of the sample and its sensitivity to pH changes as a result of external stresses (e.g. soil acidification, liming) can be estimated.

A multidisciplinary approach combining mineralogical analysis (X-ray diffraction) with chemical analysis, pH_{stat} leaching tests and geochemical modelling can provide information on the solid-phase speciation and reactivity of heavy metals in soils, sediments and waste materials. For example, the solid phase characterization of a mine waste using XRD yielded evidence for the occurrence heavy metal- and minerals such as anglesite (PbSO_4). The results of pH_{stat} leaching tests were supported by modelling predictions with MINTEQA2, indicating that the release of Pb could partly be explained by the dissolution of anglesite.

Besides the influence of pH on heavy metal leaching behaviour, additional information on heavy metal leachability and retention by the solid matrix in relation with variable surface charge is obtained from the kinetics of metal release during a pH_{stat} test.

1 Introduction

1.1 Assessment of pH-dependent leaching behaviour

pH is one of the key parameters that determines heavy metal mobility in soils and sediments. In many respects leaching behaviour as reflected by the pH_{stat} leaching test and related characterization leaching tests provide a better means of assessing environmental impact than analysis of total elemental composition [1]. A pH_{stat} test allows to assess how the solubility changes if *in situ* pH changes occur. Moreover, information is obtained on the potential buffering capacity of the sample and its sensitivity to pH changes as a result of external stresses (e.g. soil acidification, liming). Different types of test are available to assess pH-dependent leaching. In the United States, the TCLP (Toxicity Characteristic Leaching Procedure) is commonly used to determine the toxicity characteristics of a material. The TCLP is a batch test in which the size-reduced material is leached with acetic acid at a L/S ratio of 20 for 18 hours. This test is less suited to estimate metal release over a long period of time, especially since the extraction time for a TCLP is arbitrarily chosen (18 h). Moreover, leaching is addressed at only one pH-value.

Although buffer solutions represent a simple way to assess heavy metal mobility as a function of pH (e.g. [2]), buffer components can induce heavy metal complexation, resulting in unusually high leaching [3]. Kaupenjohann and Wilcke [4] presented a pH_{stat} titration in which ion exchange resins were used to remove reaction products. Cation-exchangers provide protons to the suspension while cations are released by pH-buffering of the soil. Manual titrations are rather unpractical and require some knowledge of the acid neutralizing capacity of the sample. Cremer and Obermann [5] introduced a computer-based titration system allowing continuous registration and fine-tuning of pH during leaching experiments. This system was used by Gäbler et al. [3] and Paschke et al. [6], who performed pH_{stat} leaching tests for 24 h. After 24 h, the suspended matter was removed from the liquid phase by centrifugation and filtration. Some standardized leaching tests also rely on pH_{stat} titrations. In the German standard leaching experiment (DIN 38 414-4), pH is kept at a preset value (pH 4-11). The L/S ratio is 10 (L/kg) and the duration is 24 hours [7]. The standardized availability

test NEN 7341 [8] uses pH_{stat} titrations at pH 7 and pH 4. To obtain a larger degree of dissolution, particle size is reduced to $< 125 \mu\text{m}$ and a solid liquid ratio of 1/50 is used. The total extraction time amounts to only 3 hours. The latter test intends to examine the availability for leaching of inorganic compounds in solid materials (waste materials, building materials, soils). The aim is to determine the amount of a component that can leach out of a material upon exposure of the material in aerobic conditions to extreme conditions (e.g. disintegration of the material or complete consumption of ANC). This test has been criticized for not promoting complete dissolution or equilibrium. Since only the final leachate is analysed and because of the short duration of the availability test, slow buffering reactions are not taken into account. The pH dependence leaching test (PrEN 14429), which has been developed by the Network for the Harmonisation of Leaching/Extraction Tests (SMT-CT96-2066) consists of parallel extractions of the material at an L/S=10 (L/kg) for 48 h at a series of pre-set pH-values. In addition, the test provides a measure of acid-base neutralization capacity (ANC/BNC). The most important difference between the above mentioned pH_{stat} tests and the pH_{stat} test used in our laboratory (see also [9]), is the longer duration of the test (96 h) and the monitoring of metal release during test. Additionally, the pH_{stat} leaching test was further optimised by adapting the concentration of the titration agent and by adjusting the interval of pH acquisition (see [10]).

1.2 Application of pH_{stat} leaching tests

During the last few decades, pH_{stat} leaching tests have been applied to assess the pH-dependent leaching behaviour of heavy metals in different types of matrices, for example: soils [4], industrially contaminated sites [9], waste materials [11], dredged sediments [10, 12], overbank sediments [2, 13] and anoxic river sediments [14]. An overview of the applications of pH_{stat} leaching tests described in literature is given in Table 1. Furthermore, pH_{stat} leaching tests have been evaluated as a tool to measure the weathering rates in soils [15]. pH_{stat} experiments are less suited to directly estimate weathering rates in soils since the continuous abrasion of mineral particles during stirring or shaking cause an overestimation of weathering rates [15]. In the nineties, the CEN (Comité

Eurpéen de Normalisation) started with the harmonization of new European leaching tests, partly based on existing leaching tests. One of these tests is the pH_{stat} test, which is used for the characterization of waste materials and building materials. Although pH_{stat} leaching tests have mostly been applied to study the leaching of heavy metals, Hirner et al. [16] used pH_{stat} leaching tests to study the leaching behaviour of organic contaminants. Besides for soils, sediments and waste materials, pH_{stat} leaching tests are also frequently used in medical research, for example to simulate the conditions in the digestive tract. This paper discusses the use and the possibilities of pH_{stat} leaching tests as a tool to assess the potential mobilisation of heavy metals from contaminated soils, sediments and waste materials.

Table 1 here

2 Materials and methods

2.1 Samples

3 sediment and soil samples with different physico-chemical characteristics and 1 waste material were selected for analysis. The soil and sediment samples originate from the floodplain of the Grote Beek river in Central Belgium, a small river contaminated by industrial activities. Sample GB(dr) is a dredged sediment, disposed on land more than 12 years ago. Samples GB(fo) and GB(cl) were sampled in a regularly inundated floodplain. Sample GB(cl) is a green clay-rich soil, sampled in the upper part (0-20 cm) of a overbank profile at a distance of 20 m from a river. Sample GB(fo) was taken from the same overbank profile, between 20 and 35 cm depth. This sample was characterised by red-brown and black colours because of the abundant occurrence of Fe-oxides and organic matter. Sample LC is a waste material from the mine tailing pond of La Calamine, in the mining district of Plombières-La Calamine (East-Belgium), where extensive Zn-Pb mining and smelting was carried out from the Middle Ages until the beginning of the 20th century.

Samples GB(cl), GB(dr) and GB(fo) were used to illustrate the pH-dependent and time-dependent leaching behaviour of elements, while sample LC will mainly be used to illustrate the approach combining pH_{stat} leaching tests with mineralogical analysis and thermodynamical modeling.

2.2 Physico-chemical and mineralogical sample characterization

2.1 General sample characterization

pH was measured in a soil/water suspension (1/2.5) (pH Hamilton Single pore electrode). Organic carbon was determined according to the Walkley and Black method [35]; effective cation exchange capacity (CEC) was analysed applying the 'silver thiourea method' [36],[37]. Total element concentrations (Al, As, Ba, Cd, Co, Cr, Cu, Ni, Pb, Zn, Fe, Mg, Mn, K and Ca) were determined after dissolution of the samples with a mixture of 3 concentrated acids (4 mL HCl_{conc}, 2 mL HNO_{3conc} and 2 mL HF_{conc}). A certified reference material (GBW07411 Soil) and sample triplicates were used for quality control. Values (in mg/kg) obtained were for Cd 25.9 (certified value 28.2±1.3), Zn: 3630 (certified value 3800±300), Ni: 22.3 (certified value: 24.2±2.1), Cu: 62.9 (certified value 65.4±4.7), Pb: 3010 (certified value 2700±100), Cr: 57.5 (certified value: 59.6±5.0) and As: 193 (certified value 205±11). Some measured values for the certified material are out of the certified range because the method used in this study (acid attack followed by ICP-MS measurement) is different from the method used to obtain the certified values (X-ray Fluorescence).

. All reagents used for analysis were of analytical grade. All glassware was acid rinsed with HNO₃ 0.2 M before usage.

Total S was determined with the Ströhlein Sulfur Analyzer (model S-mat, Carbolite Co. Ltd., Bamford-Sheffield). Grain size was determined by laser diffraction analysis (Malvern Mastersizer S long bed, Malvern, Worcestershire, UK) after removing carbonates (0.1 M HCl), iron oxides (0,5% oxalic acid, boiling) and organic carbon (35% H₂O₂, 60°C) and applying a peptizing solution (10 g/L sodium polyphosphate, boiling). A mineralogical sample characterization was conducted by X-ray diffraction (XRD, Philips[®], Co-target, $\lambda = 1.79 \text{ \AA}$). A Beckman GS-6 centrifuge was used for the separation of the extracts. A reciprocal shaker (SM) was employed to shake the samples during extractions.

2.3 pH_{stat} leaching

The pH_{stat} experiments were carried out with an automatic multtitration system (Titro-Wico Multititrator, Wittenfeld and Cornelius, Bochum, Germany). 80 g of material (< 2 mm fraction) was put in an Erlenmeyer flask together with 800 mL of distilled water and placed on a horizontal shaking device. A pH-electrode and an automatic titration dispenser were attached to each flask. The suspensions were first shaken for 30 minutes without addition of acid and then the titration was started. Previous experiments performed in our laboratory [9] demonstrated that the rapid addition of acid to the soil-water suspension could lead to an exceeding of the set-point pH. Therefore, the concentration of the titration solution was adapted to the set-point pH (pH 2: 2.5 M, pH 4: 1 M and pH 6: 0.25 M). The choice of the concentration of the titration agent was based on a rapid potentiometric titration, which was carried out to deduce the acid neutralizing behaviour of the sample. The interval of pH-acquisition was set to 200 s (instead of 1 s) to give the system enough time to react and eventually neutralise the acid before more acid was added [10].

At regular time intervals (0, 0.5, 1, 3, 6, 12, 24, 48, 72 and 96 h), a sample of the suspension was taken over a filter (0.45 μm Acrodisc, Pall, East Hills, NY) by means of a syringe attached to a flexible tube (For more details see also Van Herreweghe et al.[9]). Immediately after sampling, the sample was acidified with a drop of concentrated HNO_3 (ultrapure) to bring the $\text{pH} < 2$. Subsequently the sample was kept in a refrigerator until analysis.

2.4 Analysis of leachates

The solutions (digests from the 3-acid attack and the pH_{stat} leachates) were analysed by Flame Atomic Absorption Spectrometry (Thermo Electron Corporation S Series AA). for Ca, Fe, K and Al. For As, Cd, Cr, Cu, Mn, Ni, Pb and Zn a multi element analysis by Induced Coupled Plasma Mass Spectrometry (ICP-MS, HP 4500 series) was carried out. The samples were diluted just before analysis with 5% HNO_3 (ultrapure). Standard series were made up starting from the '10ppm Multi-Element Calibration Standard-2A in 5% HNO_3 ' (Hewlett Packard, Palo Alto, CA). An Indium (In) internal standard was applied to both samples and standards. The spectroscopic interference of

ArCl, which has the same m/z as As (75) was corrected according to the recommendations of the EPA (method 200.8, [38]). Each ICP-MS measurement was carried out with three repetitions holding relative standard deviations below five percent. Accuracy was also checked by measuring standard solutions as unknown samples. In the final leachates, dissolved organic carbon (DOC) was measured with a TOC analyser (Skalar Formacs^{HT} TOC analyser, Breda, The Netherlands); sulfate was measured by turbidimetry [39] and chloride and phosphate by colorimetry [40]. Electrical conductivity (18.34 EC-meter, Eijkelkamp, The Netherlands) and redox potential (Mettler Toledo Pt 4805-S7/165 Combination redox electrode, Zaventem, Belgium) were also determined.

3 Theory and calculation

3.1 Mathematical and geochemical modelling

ANC and leaching of metals as a function of time was described mathematically by the use of MATLAB software (The Mathworks, Natick, MA).

ANC curves obtained in the pH_{stat} tests with continuous setpoint titration were described according to Schwarz et al. [20]. The proton buffering capacity of soils during pH_{stat} experiments can be described as the sum of two independent first-order reactions, i.e.:

$$H_b(t) = BC_1 (1 - \exp(-k_1 t)) + BC_2 (1 - \exp(-k_2 t)) \quad (1)$$

where $H_b(t)$ (mmol/kg) corresponds to the buffered protons at time t , BC_i (mmol/kg) is the buffering capacity of system i , k_i (h^{-1}) is the rate coefficient of the buffer system i and t (h) is the time after starting the titration.

Analogously, the cumulative release of an element m at time t is given by:

$$RL_m(t) = RC_1(1 - \exp(-r_1 t)) + RC_2(1 - \exp(-r_2 t)) \quad (2)$$

With RC_i (mg/kg) is the release capacity of buffer system i , r_i (h^{-1}) is the rate coefficient of the buffer system i and t is the time after starting the titration. The release capacities of the two buffer systems

(RC₁ and RC₂) can be considered as two dominant sinks for heavy metals from which elements are released with a different rate. It has to be noticed that the two 'buffer systems' or 'pools' are only operationally defined and that they are not automatically related to classical waste or sediment components. Mathematically, it is possible to describe the cumulative release of an element with more exponential equations, but this does not result in a significantly better fit. Additionally, since a clear link with classical sediment or waste components (e.g. elements bound by inner and outer sphere complexes, minerals that can dissolve upon titration) is missing, the definition of more than two buffer systems would not lead to a more comprehensive interpretation of the results of the leaching test. Therefore, in the present work, two compartments, namely a 'labile' and a 'slowly labile' pool are considered. Besides the quantification of a 'labile' and 'slowly labile' pool of metals, each 'pool' is characterized by a release constant (k_i).

Additionally, it should be mentioned that, in some cases, the release patterns are not consistent with the two exponentials "model".

This mathematical modeling will only be discussed for the samples from the Grote Beek river (GB(cl), GB(fo), GB(dr)).

Geochemical modelling was performed with the thermodynamical speciation model MINTEQA2 4.02 [41]. The datasets included in MINTEQA were used for the calculations.

3.2 Patterns of metal release as a function of time

In general, 5 different types of heavy metal leaching behaviour as a function of time can be observed during pH_{stat} leaching tests (Fig. 1).

Figure 1 here

- **Type 1:** elements are rapidly released at the beginning of the experiment (e.g. Mg, Na, K); the 'labile' pool is by far dominant and likely related to cation exchange reactions

- **Type 2:** some elements display an initially rapid release, followed by a slow but substantial release in the final stage of the experiment. The 'labile' pool is more important than the 'slowly labile' pool ($RC_1 > RC_2$ in equation 2). This pattern is typical for the more mobile metals in the soils (Cd, Zn, Ni) that are easily desorbed upon acidification or indicates the dissolution of poorly stable solid phases (e.g. carbonates)
- **Type 3:** elements are released more slowly. In this case, the 'slowly labile' pool is more significant than the labile pool ($RC_1 < RC_2$ in equation 2). This release pattern points to the desorption of elements that are more strongly bound to soil constituents (e.g. Pb, Cr, Cu and Co) or to the slow dissolution of solid phases such as Fe-oxides. Sometimes, the release was linear as a function of time or could be described with only one exponential equation ($r_1 = r_2$ in equation 2).
- **Type 4:** some elements exhibit readsorption (As, P, which occur as anions in soil) or precipitation behaviour (e.g. Ba precipitates as $BaSO_4$).
- **Type 5:** during combined oxidation and pH_{stat} leaching of anoxic sediments, the release of metals often only starts after a certain period of time (between 6 and 48 h) ([14]). This due to the slow oxidation kinetics of heavy metal sulphides.

4 Results and discussion

4.1 General sample characteristics

The 3 soils and sediments have a average neutral pH and an elevated Fe- and organic matter content (Table 2). Elevated Cd-, As- and Zn- concentrations were detected in all the sediments. The dredged sediment (GB(dr)) has the highest heavy metal concentrations and is also contaminated with Cu and Ni. The high amount of clay in sample GB(cl) is both reflected in the elevated Al-content and in the grain size distribution (Table 2), while the K-content is consisted with the occurrence of glauconite. A mixed layer illite-smectite clay mineral was also identified in this sample. Glauconite and quartz were found in the 3 samples. Sample GB(fo) contained hematite and pyrrhotite.

The waste material from the mine tailing pond of La Calamine (sample LC) contained elevated concentrations of Pb, Zn, As and Cd. XRD analysis of this sample revealed the occurrence of quartz, kaolinite, illite, calcite, cerrusite, pyrite, marcassite and anglesite.

Table 2 here

4.2 Leaching as a function of pH

Different patterns of leaching as a function of pH were observed during the pH_{stat} test (Fig. 2). The leaching of Cd, Zn, Cu, Ni, Mn, Ca and Fe increased with decreasing pH, although a non negligible amount of these elements was also leached in the alkaline pH range, especially Cu, Ni and Fe. The solubility of Cd and Ni (relative to total concentration) as a function of pH is very similar for the different samples. In sample GB(fo), Zn is more soluble at high pH-values than in samples GB(dr) and GB(cl); Cu is characterized by a lower solubility in the pH-range 2-6 in sample GB(fo).

Figure 1 here

In soils and sediments, the solubility of heavy metals and As as a function of pH can usually be explained by the variation in surface charge as a function of pH. At pH-values above the PZC (Point of Zero Charge), the soil or sediment surface is negatively charged; pH-values below the PZC result in a positively charged surface. This explains why cationic metals (e.g. Cd, Zn, Ni, Cu) are generally more soluble at low pH-values. However, complex formation with DOC can keep metals in solution at alkaline pH-values. Fe-(hydr)oxides have a pH_{PZC} in the range 6.3 – 9.1. The pH_{PZC} of quartz is 2 [42], but in sample GB(fo), quartz grains are coated with Fe-(hydr)oxides. Moreover, all the samples are characterised by an elevated organic carbon content, which tends to decrease the pH_{PZC} .

Since As occurs as arsenate in oxidized soils and sediments, a higher solubility is generally observed as pH increases. Nevertheless, the considerable solubility of As in the acid pH-range in sample GB(dr) (and GB(cl) to a lesser extent) (Fig. 2) cannot be explained by a variable surface charge as a function of pH. The increased solubility of As in sample GB(cl) at pH 2 is most likely

due to the dissolution of clay minerals at low pH. Goldberg [43] also observed a decreased sorption of arsenate on clay minerals (illite, montmorillonite and kaolinite) at pH-values below 4.

Figure 2 here

The solubility of DOC and anions (Fig. 3) generally increased with increasing pH, although the release of Cl^- was hardly influenced by pH. The behaviour of PO_4^{3-} and DOC was different in sample GB(dr), since a considerable leaching of PO_4^{3-} and DOC was observed at low pH. The release of heavy metals from soils and sediments is to a large extent determined by the release of dissolved organic carbon. Organic carbon can bind metals and organic contaminants, whereas dissolved organic carbon can mobilise metals and organic contaminants.

The release of heavy metals from soils and sediments is to a large extent determined by the release of dissolved organic carbon. Organic carbon can bind metals and organic pollutants, whereas dissolved organic carbon can mobilise metals and organic contaminants.

DOC is a sum of parameters for all organic species in solution, such as sugars, organic acids, amino acids, lignin and humic and fulvic acids, but in natural soil systems, humic and fulvic acids control heavy metal binding. Fulvic acids are soluble under acid and alkaline conditions, while humic acids are only soluble under alkaline conditions. Generally, the solubility of DOC increases with increasing pH. However, aquatic sediments contain a higher proportion of fulvic acids than terrestrial soils and sediments, which is reflected in the important solubility of organic matter at low pH-values [44].

4.3 Assessment of equilibrium conditions

Two types of laboratory leaching tests can be distinguished : single batch tests and flow-through (“dynamic”) leaching tests. Batch extraction tests typically involve mixing a sample with a specific amount of leaching solution without renewal of the leaching solution (Washington State Department of Ecology, 2003). The mixing is performed over a relatively short time period (hours to days) with

the aim of reaching equilibrium conditions. [44]. Chemical equilibrium is reached when there is no concentration gradient at all between the porewater and the free water volume [44]. The mathematical description of leaching behaviour in pH_{stat} leaching tests allows an estimation of equilibrium conditions, assuming that metal release during pH_{stat} leaching will be at equilibrium at $t = \infty$. As a consequence, the reactive pool of an element released at a certain pH-value is given by $RC = RC_1 + RC_2$ ($t = \infty$ in equation 2). In Fig. 4, the release of Cd from the clayey soil (GB(cl)) has reached more or less a plateau phase, suggesting equilibrium conditions.

Figure 3 here

Consequently, the depletion of the reactive pool (= sum of 'labile' and 'slowly labile' pool) for Cd in sample GB(cl) is almost completed during the test. In sample GB(fo), however, leaching of Cd proceeds more slowly and equilibrium is not reached within the duration of the pH_{stat} test, since only 85% of the 'labile' and 'slowly labile' Cd is released after 96 h (Fig. 4).

Release rate of heavy metals during pH_{stat} leaching

As pH increases from 2 $\rightarrow$ 4 $\rightarrow$ 6 in the respective pH_{stat} experiments, the release rate of most elements decreases, which is quantified by mathematical fitting according to Equation 2.

In the dredged sediment GB(dr), Zn, Cd, Ni and Cu show a rapid initial release at *pH 2 and 4*, ($r_1 = 0.4\text{-}0.3\text{ h}^{-1}$) while the second buffer system, according to Equation 1, is characterised by a release rate that is an order of magnitude lower ($r_2 = 0.02\text{-}0.03\text{ h}^{-1}$) (Table 3).

The leaching curve of Zn, Cd, Ni and Cu at pH 2, 4 and 6 follows the same pattern as the ANC curve. The amount of cations released is however higher than the amount of protons introduced into the system (ANC). This was also observed by Schwartz et al. [20]. Arsenic (Fig. 6) has a somewhat different behaviour since the maximal release of these elements occurs after 6 hours, after which their concentrations in the solution start to decrease. Readsorption of negatively charged arsenate and phosphate ions on the positively charged soil surface can explain the behaviour of As. The decrease in Ba concentrations with time, which is less pronounced than for As, seems to be caused by the precipitation of $BaSO_4$. While the negatively charged sediment

surface, explains for the release of As and P at *pH* 10 in the dredged sediment, complexation with DOC keeps Cu in solution.

Table 3 here

Desorption of heavy metals at *pH* 2 in sample **GB(fo)** could be described by only 1 exponential equation (1 buffer system), with a rather slow release rate ($r = 0.02\text{--}0.08 \text{ h}^{-1}$) compared to sample GB(dr) (Table 3). The release of Fe, Cu (Table 3) and Pb at *pH* 2 is even linear as a function of time. The gradual release of Fe may indicate a slow dissolution of Fe-(hydr)oxides and the concomitant release of associated (coprecipitated) elements. At *pH* 4, the release of Zn, Cd and Ni could be described as a sum of two exponential equations, but the slow release was by far dominant. Only 7.5 % of the total amount of Cd present in sample GB(fo) was leached and almost no Fe was released. The extra amount of Cd leached at *pH* 2 was probably released as a result of the dissolution of poorly stable Fe-(hydr)oxides, as suggested by the release of Fe at *pH* 2.

Leaching of most elements at *pH* 10 in sample GB(fo) started after 48 h (Fig. 5b). While a decrease in Ca-concentrations (because of precipitation reactions and/or sorption to the negatively charged soil surface) was observed in the initial stage of the experiment, an increase in Ca-concentrations also occurred from $t = 48 \text{ h}$ onwards. After 71 h, a break appeared in the BNC curve (Fig. 5b), suggesting the start of new base neutralizing reactions. The elevated DOC-concentrations indicate a considerable dissolution of organic matter, so that a complexation of heavy metals with DOC can be expected. MINTEQA2 modelling, however, indicates that the speciation of Ni and Zn at *pH* 10 is dominated by hydroxy-complexes ($\text{Zn}(\text{OH})_{2\text{aq}}$ en $\text{Ni}(\text{OH})_{2\text{aq}}$), while Cd mainly occurs as chlorohydroxy-complex ($\text{Cd}(\text{OH})(\text{Cl})$).

Figure 4 here

In sample **GB(cl)**, the initial heavy metal release was always faster than in samples GB(dr) and GB(fo), which is expressed by the higher release constant (r_1 , Table 3).

The slow release constant (r_2) of Zn, Cd, Ni, Cu and As at different pH-values is very similar for the 3 samples (Table 3). As mentioned before, the mathematical description of heavy metal release allows a kinetic fractionation of metals into a labile (RC_1) and a slowly labile (RC_2) pool. In sample GB(dr) and GB(cl) (Fig. 4), the labile and slowly labile pool of Cd are more or less equally important, while in sample GB(fo) the slowly labile pool is dominant, resulting in a much slower overall release (RC) of Cd. behaviour during pH_{stat} leaching (Fig. 4). The same was observed for Zn and Ni at pH 4 (results not given). The considerable amount of Fe released at pH 2, suggests the dissolution of Fe-(hydr)oxides in sample GB(fo), which can explain for the slower release kinetics of Cd, Zn and Ni. The differences in mineralogy and the associated differences in charge density can also contribute to the differences in release kinetics.

Analogously to the pH_{stat} titration at pH 2, the release rate (r_1) of As and Cu from the labile pool at pH 10 is faster for sample GB(cl) than for sediment GB(dr). The release rate (r_2) of Cu and As from the slowly labile pool (r_2) is similar in both samples (Table 3). Sample GB(fo) and GB(cl) display a similar leaching pattern as the BNC, indicating that the release of As (as arsenate) is proportional to the amount of OH^- added to the suspension (Fig. 6). The solubility of Cu also evolves proportionally with BNC. The atypical BNC-curve of sample GB(fo) (Fig. 6) is composed of two parts, which could be interpreted as two 'sinks' or 'pools'. Accordingly, the release of As and Cu follows a similar pattern. A higher release of DOC (as indicated by the yellow colour of the (filtered) suspension at $t = 72, 96$ and 176 h) towards the end of the pH_{stat} test suggests that the second pool is related with the dissolution of organic matter.

It should be noticed that only a relatively small amount of As is released at pH 10 from the 3 samples (less than 6% of its total concentration, confirming the relatively low mobility of As). Nevertheless, From a practical point of view, investigation of heavy metal release at alkaline pH-values, can be used to estimate the consequences of liming, a measure that is often recommended to immobilise heavy metals in contaminated soils. The mobilisation of Cu from GB(cl) and GB(fo) is relatively important (resp. 18% and 13% of the total concentration). Consequently, an increase in

soil pH will cause an immobilisation of Cd and Zn, but the mobility of Cu, whose total concentration is not especially of concern in samples GB(cl) and GB(fo) (26 and 11 mg/kg resp.), will significantly increase upon alkalisation because of complex-formation of Cu with DOC.

Figure 5 here

4.4 Combination with mineralogical analysis and thermodynamical modelling

After pH_{stat} leaching of sample LC, the residual sample was dried and analysed with XRD. At low pH-values (pH 2 and 4), no heavy metal containing minerals disappeared from the sample. At alkaline pH, however, anglesite was removed from the sample (Fig. 7). However, almost no Pb was measured in the pH_{stat} leachate at pH 10. Geochemical modelling of heavy metal release as a function of pH was carried out with the speciation code MINTEQA2 (Fig. 8). Therefore, it was assumed that all the sulphate released at pH 10 came from the dissolution of anglesite and the sulphate concentrations were used to calculate the amount of anglesite in the sample. Hereafter, the solubility of anglesite as a function of pH was modelled. The results showed that anglesite is indeed completely dissolved at pH 10, but Pb precipitates again as Pb-(hydr)oxides, explaining for the very low Pb-concentration found in the leachate at pH 10. According to the MINTEQA-calculations, a partial dissolution of anglesite occurs at pH 2 and 4, but XRD-analysis indicates that the dissolution of anglesite is not significant at acid pH-values.

Figure 6 here

Figure 7 here

Prediction of soil acidification

The total acid deposition by rain amounted in Flanders in 2005 to 3810 equivalents of acid per hectare and per year [45]. Assuming quasi constant emissions of SO_x, NO_x and NH_x compounds in the coming years and accepting that ANC is correctly estimated after 96 h leaching, future contaminant leaching can to some extent be predicted. If one ha is considered and a soil layer of 20 cm is taken into account, the mass of this volume can be calculated. Bulk density values for the

sandy loam samples of 1.30 (ton/m³) were used. The time to reach a certain acid neutralization can be calculated by applying the following equation:

$$Time(years) = \frac{ANC_{96h} (mmol / kg)}{\left[3810 \times 1000 \left(\frac{mmol}{ha * y} \right) \right] / mass(kg / ha)} \quad (3)$$

It must however be kept in mind that these results should be considered as a worst case scenario since the considered experimental conditions do not occur in nature. The experimental results suggest that sample GB(cl) is most sensitive to acidification (Table 4). In less than 100 years, soil pH can decrease to a value of 4, resulting in a considerable release of Cd and Zn. Sample GB(fo) is less sensitive to acidification. Moreover, this sample was collected in an overbank profile below the clay-rich soil sample and we can expect that acidification will first affect the upper part of the soil. The dredged sediment (GB(dr)), which displays the highest total metal concentrations, is also characterised by a considerable acid neutralizing capacity. According to the calculations (Equation 3), acidification to pH 6 as a consequence of acid deposition can occur in less than 50 years, but will not release important heavy metal concentrations. Further acidification will lead to a more important heavy metal release, but this will only occur after a long period of time (e.g. 433 years to reach pH 4) because of the favourable ANC of the sediment.

Table 4 here

Based on the acid neutralizing capacity of the sample from the waste material LC, heavy metal release upon acidification of the tailing material can be predicted. On medium long term (± 100 years) a rather limited release of Pb (± 4 mg/kg) has to be expected upon acidification. For Zn, however, more than 900 mg/kg could be released in a time span of 100 years as a consequence of acid deposition.

5 Conclusions

- Based on pH_{stat} leaching tests, an insight in heavy metal mobility in soils, sediments and waste materials as a function of pH is obtained and reactions occurring during acidification and alkanilisation are derived. Mathematical description of leaching behaviour as a function of time enables to distinguish between groups of elements with a different leaching behaviour, which can also be interpreted in terms of 'pools' of different reactivity. Additionally, pH_{stat} titrations allow a determination of acid neutralizing capacity, making it possible to predict heavy metal release upon acidification, assuming a worst-case scenario.
- A multidisciplinary approach combining solid-phase characterization (e.g. by X-ray diffraction, SEM-EDX) and geochemical modelling with chemical analysis and pH_{stat} leaching tests can provide information on the composition of soils, sediments and waste materials and the reactivity of heavy metals in these matrices. Besides the solid phase characterization of a material, the results of pH_{stat} leaching tests can be supported by modelling predictions with thermodynamical codes (e.g. MINTEQA).
- The European pH_{stat} test, which is currently being standardized within the CEN framework (CEN-TC292/WG6,) consists of a 48 h pH_{stat} test at 8 different pH-values in the range 4-12 [26]. Whereas, based on practical considerations, only the final leachate (after 48 h) is analysed, the analysis of the leachate at different time intervals is interesting because it allows to assess the kinetics of metal release. Additionally, the analysis of 'matrix elements', such as Fe and Ca, can provide information concerning the processes responsible for the release of contaminants.

6 Acknowledgements

We acknowledge Danny Coutermans for his assistance with the experiments. This research was financed by the Research Foundation of the K.U.Leuven.

7 References

- [1] H.A. van der Sloot, R.N.J. Comans, O. Hjelm, Similarities in the leaching behaviour of trace contaminants from waste, stabilized waste, construction materials and soils. *Sci. Total Environ.* 178 (1996) 111-126;
- [2] S.L. Tackett, E.R. Winters, M.J. Puz, Leaching of metals from sewage sludge: pH effects. *Can. J. Soil Sci.* 66 (1986) 763-765.
- [3] H.E. Gäbler, Mobility of heavy metals as a function of pH of samples from an overbank sediment profile contaminated by mining activities. *J. Geoch. Explor.* 58 (1997) 185-194.
- [4] M. Kaupenjohann, W. Wilcke, Heavy metal release from a serpentine soil using a pHstat technique. *Soil Sci Soc Am J* 59 (1995) 1027-1031.
- [5] S. Cremer, P. Obermann, Mobilisierung von Schwermetallen in Porenwassern von belasteten Böden und Deponien: Entwicklung eines aussagekräftigen Elutionsverfahrens. Landesamt für Wasser und Abfall Nordrhein-Westfalen (Hrsg.), Materialien zur Sanierung und Ermittlung von Altlasten, Band 6, Düsseldorf, 1992
- [6] A. Paschke, R. Wennrich, P. Morgenstern, Comparison of 24h and long-term pHstat leaching tests for metal mobilization from solid matrices. *Acta Hydrochim. Hydrobiol.* 27 (1999) 223-229.
- [7] K. Hamer, V. Karius, Brick production with dredged harbour sediments. An industrial scale experiment. *Waste Management* 22 (2002) 521-530.
- [8] NEN7341, Leaching characteristics of solid earthy and stoney building and waste materials. Leaching tests. Determination of availability of inorganic compounds for leaching. 1st edition, February 1995, Delft, 10pp.
- [9] S. Van Herreweghe, R. Swennen, V. Cappuyns, C. Vandecasteele. Speciation of heavy metals and metalloids in soils: an integrated study near former ore treatment plants with emphasis on pH_{stat}-leaching. *J. Geoch. Expl.* 76 (2002) 113-138.
- [10] V. Cappuyns, R. Swennen, A. Devivier. Influence of ripening on pH_{stat} leaching of heavy metals from dredged sediments. *J. Environ. Monit.* 6(9) (2004a) 774-781.
- [11] P. Ganne, V. Cappuyns, A. Vervoort, L. Buvé, R. Swennen. Leachability of heavy metals and arsenic from tailings of metal treatment industry at Angleur (eastern Belgium). *Sci Total Environ* 356(1-3) (2005) 69-85.
- [12] T. Lager, K. Hamer and H.D. Schulz. Mobility of heavy metals in harbour sediments: an environmental aspect for the reuse of contaminated dredged sediments. *Environ. Geology* 48(1) (2005) 92-100.

- [13] V. Cappuyns, R. Swennen. Secondary mobilisation of heavy metals in overbank sediments. *J. Environ. Monit.* 6(5) (2004) 343-340.
- [14] V. Cappuyns, R. Swennen. Kinetics of element release during combined oxidation and pH_{stat} leaching of anoxic river sediments. *Appl. Geochem.* 20(6) (2005) 1169-1179.
- [15] J.J.M. van Grinsven, W.H. van Riemsdijk. Evaluation of batch and column techniques to measure weathering rates in soils. *Geoderma* 52 (1-2) (1992) 41-57.
- [16] A.V. Hirner, F.M. Pestke, U. Busche, A. Eckelhoff. Testing contaminant mobility in soils and waste materials. *J. Geoch. Expl.* 64 (1988) 127-132.
- [17] A.M. Fällman, B. Aurell. Leaching tests for environmental assessment of inorganic substances in wastes, Sweden. *Sci. Total Environ.* 178 (1996) 71-84.
- [18] U. Förstner, I. Haase. Geochemical demobilization of metallic pollutants in solid waste-implications for arsenic in waterworks sludges. *J. Geoch. Expl.* 62 (1998) 29-36.
- [19] J.A. Meima and R.N.J. Comans. The leaching of trace elements from municipal solid waste incinerator bottom ash at different stages of weathering. *Appl. Geochem.* 14 (1999) 159-171.
- [20] A. Schwarz, W. Wilcke, W. Zech. Heavy metal release from batch pH_{stat} experiments. *Soil Sci. Soc. Am. J.* 63 (1999) 290-296.
- [21] H-E. Gäbler, J. Schneider. Assessment of heavy-metal contamination of floodplain soils due to mining and mineral processing in the Harz Mountains, Germany. *Environ. Geol.* 39(7) (2000) 774-782.
- [22] V. Karius, K. Hamer. pH and grain-size variation in leaching tests with bricks made of harbour sediments compared to commercial bricks. *Sci. Total Environ.* 278 (1-3) (2001) 73-85.
- [23] H.A. van der Sloot, D. Hoede, D.J.F. Cresswell, J.R. Barton. Leaching behaviour of synthetic aggregates. *Waste Management* 21(3) (2001) 221-228.
- [24] H.A. van der Sloot. Characterization of the leaching behaviour of concrete mortars and of cement-stabilized wastes with different waste loading for long term environmental assessment. *Waste Management* 22(2) (2002) 181-186.
- [25] H. Ecke, Sequestration of metals in carbonated municipal solid waste incineration (MSWI) fly ash. *Waste Management* 23(7) (2003) 631-640.
- [26] J.L.T. Hage, E. Mulder. Preliminary assessment of three new European leaching tests. *Waste Management* 24 (2004) 165-172.

- [27] J.J. Dijkstra, J.C.L. Meeussen; R.N.J. Comans. Leaching of Heavy Metals from Contaminated Soils: An Experimental and Modeling Study. *Environ. Sci. Technol.*, 38 (16) (2004) 4390 - 4395.
- [28] J.J. Dijkstra, H.A. van der Sloot., R.N.J. Comans. The leaching of major and trace elements from MSWI bottom ash as a function of pH and time. *Appl. Geochem.* 21(2) (2006) 335-351.
- [29] H. Ecke, A. Åberg, Quantification of the effects of environmental leaching factors on emissions from bottom ash in road construction. *Sci. Total Environ.* 362(1-3) (2006) 42-49.
- [30] A.L. Guimaraes, T. Okuda, W. Nishijima, M. Okada. Organic carbon leaching behavior from incinerator bottom ash. *J. Hazard. Mat.* 137(2) (2006) 1096-1101.
- [31] H.A. van der Sloot, A. van Zomeren, J.C.L. Meeussen, P. Seignette, R. Bleijerveld. Test method selection, validation against field data, and predictive modelling for impact evaluation of stabilised waste disposal. *J. Hazard. Mat.* 141(2) (2007) 354-369.
- [32] A. Herre, F. Lang, Ch. Siebe, R. Dohrmann, M. Kaupenjohann, Mechanisms of acid buffering and formation of secondary minerals in vitric Andosols. *Eur. J. Soil Sci.* 58(2) (2007) 431-444.
- [33] L. Horckmans, R. Swennen, J. Deckers Retention and release of Zn and Cd in spodic horizons as determined by pHstat analysis and single extractions. *Sci. Total Environ.* 376 (1-3) (2007) 86-99.
- [34] P. Chaurand, J. Rose, J. Domas, J.-Y. Bottero. Speciation of Cr and V within BOF steel slag reused in road constructions. *J. Geochem. Expl.* 88(1-3) (2006) 10-14.
- [35] D.W. Nelson, L.E. Sommers, Total carbon, organic carbon, and organic matter. In: A.L. Page, R.H. Miller, and D.R. Keeney (eds.), *Methods of Soil Analysis. Part 2: Chemical and Microbiological Properties*. 2nd ed. American Society of Agronomy, Madison, WI, pp. 538-580, 1982.
- [36] R. Chhabra, J. Pleysier, and A. Cremers. The measurement of the cation exchange capacity and exchangeable cations in soils: A new method. p. 439–449. In *Proc. of the Int. Clay Conf.*, 16–23 July 1975. Mexico City. Applied Publishing Ltd., Wilmette, IL., 1975.
- [37] L.P. Van Reeuwijk. *Procedures for soil analysis* - 3rd ed. Wageningen : ISRIC, 1992.
- [38] C.A. Brockhoff, J.T. Creed, T.D. Martin, E.R. Martin, S.E. Long. EPA Method 200.8, Revision 5.5: Determination of trace metals in waters and wastes by inductively coupled plasma-mass spectrometry, EPA-821R-99-017, October 1999, 61 pp.
- [39] A.I. Vogel. Nephelometric determination of sulfate. In: *Quantitative inorganic analysis*, 1961, pp 850-851

- [40] P.G. Jeffery. Chemical methods of rock analysis, Pergamon Press, 1981, p 193-194
- [41] J.D.Allison D.S. Brown, K.J. Novogradac, MINTEQA2/PRODEFA2, A chemical assessment model for environmental systems: version 4.0 user's manual. Environmental research laboratory office of research and development. US-EPA, Athens, 1999.
- [42] M. Kosmulski. pH-dependent surface charging and points of zero charge II. Update. J. Colloid Interface Sci.275 (1) (2004) 214-224.
- [43] S. Goldberg. Competitive Adsorption of Arsenate and Arsenite on Oxides and Clay Minerals Soil Sci. Soc Am J 66 (2002) 413-421.
- [44] Washington State Department of Ecology, An Assessment of Laboratory Leaching Tests for Predicting the Impacts of Fill Material on Ground Water and Surface Water Quality. Toxics Cleanup Program Olympia, Washington 98504-7600, December 2003. Publication No. 03-09-107.
- [45] MIRA-T. (2005). Milieurapport Vlaanderen Milieuindicatoren in zakformaat. Vlaamse Milieumaatschappij, 2005. www.milieurapport.be

Table captions

Table 1: Application of pH_{stat} leaching test for soils, sediments and waste materials (ordered by year of publication)

Table 2: Physico-chemical and mineralogical characteristics of samples GB(dr), GB(fo), GB(cl) (mean $\pm$ standard deviation of 3 replicates) LC 10 and LC19. Q=quartz, gl=glaucanite, am=amorphous

Table 3: Parameters from the fitting of heavy metal release according to Equation 2. (number of data points=1730, R is significant at $\alpha=0.05$)

Table 4: Release of Ni, Cu, Zn, As and Cd (in mg/kg dry matter) and ANC at pH 2, 4 and 6 and at natural soil pH ('soil') after 96 h of pH_{stat} leaching. 'pH' is the pH at which the pH_{stat} leaching test was performed, 'Time' gives the time necessary to reach a certain ANC according to equation (3).

Tables

8 Table 1

Ref.	Material	Elements analyzed	L/S	Duration of the test	pHs investigated
[16]	Soil, tar coke, waste, shredder material	n-alkanes, PAHs, PCBs	50	1 h	pH 4 and pH 10
[15]	Soil	K, Na, Ca, Mg, Al, Si, Cl, SO ₄ , NO ₃	6	10 days	pH 3
[4]	Soil	Al, Fe, Ca, Mg, K	10	96 h	pH 3
[17]	Waste material: slag and ashes				
[2]	Floodplain soils	Pb, Cu, Zn and Cd	10	24 h	
[18]	Solid waste materials and waterwork sludges	Fe, Mn, As, Cu, Zn, Ni	10	24 h	pH 4 and pH 11
[19]	Incinerator bottom ash	Mo, Cu, Zn, Cd, Pb	5	24 h	pH 4-12
[20]	Soils (A-horizons)	Cd, Pb, Cu, Zn, Ni, Cr	10	10 to 96 h	pH 3
[6]	Waste of copper mining, topsoils, sediments	As, Cd, Cr, Cu, Fe, Mn, Ni, Pb, Zn	10	24 h and > 170 h	pH 4
[21]	Floodplain soils	Pb, Cd, Zn, Cu	10		pH 3.5, 5, 6.2
[22]	Bricks	Mg, Ca, V, Cr, Mn, Ni, Cu, Zn, As, Sr, Cd, Ba, SO ₄ , K and Mo	10	24 h	pH 4, 5, 6, 7 and 11
[23]	Synthetic aggregates	Al, B, Ca, K, Li, Mg, Mb, P, S, Si, Sr	10	48 h	pH 4-13
[24]	Concrete mortars Cement-stabilized waste	Al, Ba, Ca, Cd, Cl, Cr, K, Mb, Pb, S, Si, V, Zn	10	24 h	pH 2-10
[9]	Soils of heavily contaminated sites	Mg, Ca, Mn, Fe, Al, V, Cr, Fe, Co, Ni, Cu, Zn, As, Se, Cd, Pb	10	0 to 96 h	pH 1,3,5,7,9,11
[25]	MSWI fly ash	Pb, Zn, Cd, Cr, Cu, Ni, Mn, Al, Mg, Ba, As	40	12 h	pH 4.5 and pH 8.3
[26]	Residue from brick industry	Zn, Se, F, Cl, SO ₄ , Br electrical conductivity	10	24h	pH 4-12 (8 values)
[10]	Dredged sediments	Mg, Ca, Mn, Fe, Al, V, Cr, Fe, Co, Ni, Cu, Zn, As, Se, Cd, Pb, DOC, DIC, SO ₄ ²⁻ , PO ₄ ³⁻	10	0 to 96 h	pH 2,4,6,8,10
[27]	Contaminated soils	Ni, Cu, Zn, Cd, and Pb	10	24 h	pH 0.4-12
[28]	MSWI bottom ash	Al, Ca, SO ₄ , Mg, Si, Fe, Na and DOC	10	3,6,24,48, 168 h	pH 4,6,8,10,12
[29]	Bottom ash used in road construction	Cd, Cr, Cu, Nu, Pb, Zn, DOC, Cl-	10 50	NM	pH 7 and pH 10
[30]	Incinerator bottom ash	DOC, Ca, Al, Si	100	2 h	pH 4,6,7,8 ,9,11
[11]	Mine waste	Mg, Ca, Mn, Fe, Al, V, Cr, Fe, Co, Ni, Cu, Zn, As, Se, Cd, Pb	10	0 to 96 h	pH 2,4,6,8,10
[31]	Stabilized waste samples	EC, Mo, Cd, Zn, Cu, Pb, V, Ca, K, SO ₄ ²⁻ , P, CO ₃ ²⁻	10	48 h	pH 2-13
[32]	Vitric andosols	Al, Si, Ca, Mg, Na, DOC	10	24 h	pH 3
[33]	Cd- and Zn-contaminated Podzols	DOC, Al, Ca, Fe, Zn, Cd	10	0 to 96 h	pH 2,3,5,8
[34]	Slags reused in road construction	V, Cr	30	47 days	pH 5

NM = not mentioned

EC = electrical conductivity

Table 2

	Zn mg/kg	Ni mg/kg	Cd mg/kg	Cu mg/kg	As mg/kg	Pb mg/kg	Mn mg/kg
GB(dr)	4083 ± 345	84 ± 54	213 ± 16	182 ± 11	254 ± 25	54 ± 2	527 ± 17
GB(fo)	320 ± 13	36 ± 67	40 ± 2	11 ± 1	196 ± 4	67 ± 1	122 ± 6
GB(cl)	545 ± 12	20 ± 30	11 ± 0,4	26 ± 1	103 ± 2	30 ± 1	64 ± 2
LC	108100	ND	297	60	1491	20600	4843
	Ba mg/kg	Fe %	Ca %	Al %	S %	K %	Org C %
GB(dr)	709 ± 28	8.2 ± 1.0	1.67 ± 0.17	1.21 ± 0.01	0.35 ± 0.02	0.80 ± 0.02	8.8 ± 1.0
GB(fo)	199 ± 4	14.7 ± 0.5	0.51 ± 0.03	1.33 ± 0.10	0.57 ± 0.03	0.66 ± 0.03	9.0 ± 1.0
GB(cl)	69 ± 3	11.9 ± 0.6	0.26 ± 0.04	3.38 ± 1.06	0.16 ± 0.01	3.26 ± 1.20	5.3 ± 0.4
LC	ND	11.77	4.72	3.08	13	1.06	ND
	CEC cmol/kg	pH (H₂O)	clay %	silt %	sand %	Mineralogy	
GB(dr)	19 ± 0,5	6.8 ± 0.2	45	42	13	Quartz, glauconite, am. Fe-hydroxides	
GB(fo)	31 ± 0,6	6.3 ± 0.2	21	29	50	Quartz, glauconite, hematite, pyrrhotite	
GB(cl)	33 ± 0,6	6.4 ± 0.2	81	15	4	Quartz, glauconite, illite, smectite	
LC	ND	6.4 ± 0,2	59	37	4	Quartz, kaolinite, illite, calcite, cerrusite, pyrite, marcassite, anglesite	

ND= not determined

Table 3

			RC₁	RC₂	r₁	r₂	R	¹RC_{depleted}
			%	%	h ⁻¹	h ⁻¹		%
pH 2	Zn	GB(dr)	87	16	0.38	0.02	0.993	97
		GB(fo)		102		0.03	0.987	98
		GB(cl)	67	31	4.06	0.08	0.999	102
	Cd	GB(dr)	81	21	0.33	0.03	0.995	98
		GB(fo)		105		0.02	0.992	95
		GB(cl)	62	37	3.49	0.12	0.999	102
	Ni	GB(dr)	69	57	0.43	0.01	0.993	80
		GB(fo)	75	48	0.02	0.00	0.993	81
		GB(cl)	67	31	4.05	0.05	0.995	102
	Cu	GB(dr)	71	39	0.47	0.01	0.991	90
		GB(fo)	RC = 0.60 t + 3.7629				0.976	
		GB(cl)	35	61	3.86	0.08	0.998	103
pH 4	Zn	GB(dr)	44	62	0.26	0.03	0.999	94
		GB(fo)	19	96	0.15	0.01	0.991	87
		GB(cl)	69	31	1.64	0.04	0.998	100
	Cd	GB(dr)	53	50	0.32	0.03	1.000	97
		GB(fo)	15	102	0.43	0.01	0.994	85
		GB(cl)	47	58	1.60	0.03	0.997	95
	Ni	GB(dr)	29	75	0.28	0.03	1.000	96
		GB(fo)	19	101	0.58	0.01	0.998	83
		GB(cl)	44	53	1.57	0.04	0.989	103
pH 10	As	GB(dr)	48	53	0.37	0.04	0.997	99
		GB(cl)	44	59	1.15	0.02	0.997	97
	Cu	GB(dr)	42	58	0.34	0.04	0.998	100
		GB(cl)	50	46	1.39	0.03	0.993	104

$$^1\text{RC}_{\text{depleted}} = \text{RC}/(\text{RC}_1 + \text{RC}_2) \times 100$$

Table 4

	pH	Cd mg/kg	Ni mg/kg	Zn mg/kg	Cu mg/kg	As mg/kg	ANC mmol/kg	Time y
GB(dr)	2	140	99	4466	67	14	2331	1591
	4	10	25	347	2	6	680	464
	6	0.42	1.3	5	<0.05	0.7	64	44
	soil	0.06	0.6	0.19	0.5	0.5	-	-
GB(fo)	2	40	38	276	0.5	<0.05	994	678
	4	3	3	148	<0.05	<0.05	409	280
	6	0.1	0.39	4	<0.05	<0.05	46	31
	soil	<0.05	0.34	2	<0.05	<0.05	-	-
GB(cl)	2	8.89	6.6	240	4.8	0.08	477	326
	4	2.7	1.44	70	0.1	0.27	150	103
	6	<0.05	0.21	<0.05	0.11	<0.05	24	16
	soil	<0.05	0.14	<0.05	0.07	<0.05	-	-

Figure captions

Figure 1: Illustration of the different patterns of metal release observed during pHstat leaching tests and the fitting of metal release from 2 buffer systems or sinks (RCi).

Figure 2 Leached amount (mg/L) of Cd, Zn, Ni, as, Cu Mn, Ca, Fe and ANC-BNC as a function of pH during the pH_{stat} test after 96 h in samples GB(dr), GB(fo) and GB(cl)

Figure 3 Leached amount of DOC, DIC (dissolved inorganic carbon), PO_4^{3-} , SO_4^{2-} and Cl^- as a function of pH in samples GB(dr), GB(fo) and GB(cl) .

Figure 4: Illustration of the kinetic fractionation of Cd at pH 4 into a 'labile' (RC₁) and 'slowly labile' (RC₂) pool according to Equation 2 in samples GB(cl) and GB(fo). The release of Cd is represented as % of the calculated maximal release.

Figure 5: (a) Leaching behaviour of As in sample GB(dr), at pH 2, 4, 8 and 10 (b) Leaching behaviour of Fe, Cd and Ca and BNC in sample GB(fo) at pH 10 (% of maximal concentration).

Figure 6: BNC and release of Cu and As at pH 10 during the pH_{stat} test of samples GB(dr), GB(fo) and GB(cl).

Figure 7: XRD-pattern of sample LC before (original sample) and after pHstat leaching at pH 10.

Figure 8: Experimental and modeled solubility of Pb as a function of pH in sample LC. The model is based on the assumption that anglesite determines the solubility of Pb. See text for explanations.

Figures

Fig 1

Fig 2

Fig 3

Fig 4

Fig 5

Fig 6

Fig 7

Fig 8