Citation	Alexander Standaert, Mohadig Rousstia, Saoer Sinaga, Patrick Reynaert,(2015) Analysis and Experimental Verification of the HE11 Mode in Hollow PTFE Fibers Proceedings of 2015 Asia-Pacific microwave conference (APMC2015)
Archived version	Author manuscript: the content is identical to the content of the published paper, but without the final typesetting by the publisher
Published version	http://emfield.org/apmc2015/index.php
Journal homepage	http://emfield.org/apmc2015/index.php
Author contact	your email patrick.reynaert@esat.kuleuven.be your phone number + 32 (0)16 32 18 78

(article begins on next page)

Analysis and Experimental Verification of the HE11 Mode in Hollow PTFE Fibers

Alexander Standaert*, Mohadig Rousstia[†], Saoer Sinaga[†] and Patrick Reynaert*

*ESAT/MICAS, Katholieke Universiteit Leuven, Belgium

[†]Advanced Development Industrial, TE Connectivity Nederland B.V., The Netherlands

Abstract—This paper studies the fundamental guided mode (HE11) in hollow core polymer fibers. The effect on the effective index of the inside radius, the outside radius and the frequency is studied. Two methods were used to verify this model. Firstly the effective wavelength is measured. The effective indices calculated from the measured effective wavelengths are compared with the model. Secondly the groupdelay is measured. This is then compared to the groupdelay derived from the model. Both approaches are in good agreement with the model.

I. INTRODUCTION

In recent years, there is a growing interest in the use of dielectric waveguides for data communication at millimeter wave frequencies. Due to technology scaling, it is now possible to make RF-communication links operating at frequencies up to 120GHz [1] [2] [3]. Dielectric waveguides have the advantages to have low losses, to be flexible and cheap. They can be used for medium to short distances (1-20m) and high speed (20-1Gbps) data communications (e.g. automotive applications, HDMI cables ...). [1] [4] proposes a hollow PTFE tube as a good channel. This paper will investigate the method of propagation through this channel. As will be proven by means of measurements, it is not a leaky mode that is propagating, like is the case for tubes with a large diameter and exited at higher frequencies [5] [6]. Instead it is a guided mode which is propagating in a similar fashion as in a solid core fiber.

In the first part of this paper, we present an analysis of the effective index of the HE11 mode in a hollow core fiber. This in function of the inside radius, the outside radius and the operating frequency. In the second half of this paper a measurement technique is proposed to obtain the effective index of a mode propagating in a fiber, by measuring the effective wavelength. This method along with the groupdelay is then used to verify the model proposed in this paper.

II. ANALYSIS

The propagation constant of the HE11 mode of a hollow tube fiber with an inside radius (r_{in}), an outside radius (r_{out}) and a given frequency, can be found using the wave equation in cylindrical coordinates (1).

$$\left[\frac{1}{r} \left(\frac{\partial}{\partial r} r \frac{\partial}{\partial r} + \frac{\partial}{\partial \theta} \frac{1}{r} \frac{\partial}{\partial \theta} \right) + p^2 \right] \begin{bmatrix} E_z \\ H_z \end{bmatrix} = 0 \quad (1)$$

where

$$p^2 = \omega^2 \mu_0 \epsilon - \beta^2$$

The solution of this differential equation is well known and is divided in an radial and an azimuthal solution [7]. The

Fig. 1. Relationship between n_{eff} , r_{in} , r_{out} , λ . Lines A - C represent the frequency behavior if the r_{in}/r_{out} ratio is fixed. The r_{in}/r_{out} ratio of line A is 1/3, the ratio of line B is 1/2 and the ratio of line C is 2/3.

equation that leads to the radial solution is known as Bessel's equation. Its linearly independent solutions are known as Bessel functions and Neumann functions. An appropriate combination of these solutions should be chosen in each region of the fiber in order to be able to satisfy the boundary conditions. As suggested in [7], the axial electrical fields in the different regions in the fiber are taken as follows:

Region 1: $0 < r < r_{in}$

$$E_z^{(1)} = C_1 J_n(p_1 r) e^{jn\theta} \quad (2)$$

Region 2: $r_{in} < r < r_{out}$

$$E_z^{(2)} = C_2 J_n(p_2 r) e^{jn\theta} + D_2 Y_n(p_2 r) e^{jn\theta} \quad (3)$$

Region 3: $r_{out} < r$

$$E_z^{(3)} = G K_n(qr) e^{jn\theta} \quad (4)$$

To obtain the HE11 mode, the order of the Bessel functions is taken to be 1. The transverse fields can be obtained by filling in the axial fields in Maxwell's curl equations. At the boundaries between air and plastic the tangential fields must be continuous. This constraint leads to a set of 8 equations and 8 unknowns. In order to have a non-trivial solution to this set of equations, the determinant of the resulting matrix must

Fig. 2. Measurement setup for effective wavelength

be zero. The real solutions to this characteristic equation are the propagation constants of the various HE_{1m} modes. The solution with the highest value corresponds to the propagation constant of the HE_{11} mode. The effective index is then defined as β/k_0 , with k_0 being the freespace propagation constant. The previously described algorithm was implemented in MATLAB[®] and verified with HFSS. Figure 1 shows the results of an extensive sweep over the inside radius, the outside radius and the frequency. In these simulations, the material in the hollow core and outer cladding was vacuum. The tube material was teflon, where the relative permittivity was taken to be 2.1. In the model the r_{out} was always taken to be larger than r_{in} . The grey zone in the upper left corner of figure 1 is thus a meaningless area. In the results, the geometry has been normalised with the wavelength. Given a certain geometry, the effective index of the fundamental mode will increase with increasing frequency (decreasing wavelength). The lines A - C represent fibers with different increasing r_{in}/r_{out} ratios. As can be seen on the figure, a hollow fiber with a small r_{in}/r_{out} ratio (e.g. line A) will have a steep ascent of the effective index with increasing frequency. A hollow fiber with a big r_{in}/r_{out} ratio (e.g. line C) will have a slow ascent of the effective index with increasing frequency. This can also be seen in figure 4. The next section will demonstrate the accuracy of these lines by means of measurements.

III. EXPERIMENT

Two different approaches were tested to verify the model from section II. The first approach is to measure the effective wavelength of the mode propagating in the fiber. The second approach is to measure the groupdelay of the mode propagating in the fiber. By measuring the effective wavelength, the effective index can easily be calculated using equation 5, leading to an elegant proof. Measuring the groupdelay on the otherhand is a simple and less time consuming measurement.

$$n_{eff} = \frac{c_0}{\nu} = \frac{c_0}{freq * \lambda_{eff}} \quad (5)$$

where

c_0	Speed of light in vacuum
ν	Effective speed of the mode in the fiber
$freq$	Frequency of the wave in the fiber
λ_{eff}	Effective wavelength of the mode in the fiber

A. The effective wavelength

To measure the effective wavelength a method was used similar as in [8]. A metal sheet is placed against the fiber as shown in figure 2. The electric field of a mode propagating

(a) Measured reflected power in function of the relative position of the metal sheet (b) Distribution of the measured wavelengths

Fig. 3. Results of λ_{eff} measurement

Fig. 4. Measured n_{eff} vs simulated n_{eff}

in a dielectric fiber is not only inside the fiber but also outside the fiber. Because of this, the metal plate causes a perturbation in the wave. Due to this perturbation, a reflection is caused which interferes with the reflection at the interface between fiber and input coupler. Depending on the position of the metal sheet this interference will be constructive or destructive. The distance that the metal sheet should travel between 2 consecutive constructive/destructive interference maxima/minima, is half a wavelength. Figure 3a shows the measured reflected power of a PTFE fiber in function of the relative position of the perturbator. The measurement in figure 3 was carried out on a PTFE fiber with inside radius of 0.5mm and outside radius of 1mm. The measured frequency is 120GHz. The metal sheet is moved in steps of 10um, this leads to a resolution of the measured effective wavelength of

Fig. 5. Measured groupdelay vs simulated groupdelay

20μm. By moving the perturbator over a distance of several millimeters, multiple dips and peaks are observed, leading to a distribution of the measured effective wavelength. Figure 3b shows this distribution along with the simulated effective wavelengths of different modes that can propagate in the fiber. It is clear that the measured effective wavelength corresponds to the HE11 mode. Note that for this fiber, at 120GHz the TE and TM mode are very close to their cutoff frequency. Therefore their effective wavelength is near the free space wavelength (2.5mm).

Figure 4 shows the measured effective indexes of several different hollow fibers. The dimensions of the fibers were chosen in such a way that the r_{in}/r_{out} ratios correspond to the r_{in}/r_{out} ratio of one of the lines A – C. The measured effective indexes correspond with the simulation results quite well. Among the measured fibers, two of them have a r_{in}/r_{out} ratio of 0.5. As can be seen on the figure they both follow the trend of line B. As the frequency in a given fiber increases, there is the possibility of exciting more than one mode. The measurement results of the fiber with $r_{in} = 0.75mm$ and $r_{out} = 1.5mm$, correspond quite well with the simulation results up to a r_{out}/λ ratio of about 0.6. Afterwards the effective index drops down considerably. Comparing with simulation results of higher order modes, it is highly probable that the TM mode was then exited.

B. The groupdelay

The groupdelay of a mode in a fiber can be calculated using equation 6. This was done for the fibers corresponding with lines A – C. Each mode will have a different groupdelay.

$$\tau_g = \frac{d\beta}{d\omega} = \frac{1}{2\pi} \frac{d\beta}{df} \quad (6)$$

To measure the groupdelay, a fiber length of 1m was taken. The VNA used to excite the mode in the fiber, then automatically calculates the groupdelay based on the phase. Figure 5 illustrates the measured groupdelays vs the simulated groupdelays. The groupdelay of fibers with a small r_{in}/r_{out} ratio (e.g. line

A) will saturate quickly to a more or less constant value. A mode in a fiber propagates with a propagation constant between the propagation constant of the core and cladding. Intuitively one can see that the propagation in a solid core fiber ($r_{in}/r_{out} = 0$) will develop quickly to the propagation constant of the core with increasing frequency. This will have a near linear relationship with the frequency. The groupdelay will thus be near constant.

As was the case in the measurement of the effective index, the measurement results of the fiber with $r_{in} = 0.75mm$ and $r_{out} = 1.5mm$, shows some discrepancy compared to the simulations results. It is suspected that an other mode is exited from an r_{out}/λ ratio of 0.6 onwards. Unlike in the effective index measurement no real proof can be shown for this suspicion.

IV. CONCLUSION

The HE11 mode of hollow circular fibers has been studied. The influence of the geometry and frequency on the effective index has been investigated. The results of this model were then verified in two different ways. Firstly by measuring the effective wavelength and secondly by measuring the groupdelay. In both cases the measurement results correspond well to the simulation results. The proposed techniques and model can be used to optimize polymer channels for high speed connections.

ACKNOWLEDGMENT

This research was supported by TE Connectivity Nederland B.V.

REFERENCES

- [1] W. Volckaerts, N. Van Thienen, and P. Reynaert, "An fsk plastic waveguide communication link in 40nm cmos," in *Solid-State Circuits Conference - (ISSCC), 2015 IEEE International*, Feb 2015, pp. 1–3.
- [2] S. Fukuda, Y. Hino, S. Ohashi, T. Takeda, H. Yamagishi, S. Shinke, K. Komori, M. Uno, Y. Akiyama, K. Kawasaki, and A. Hajimiri, "A 12.5+12.5 gb/s full-duplex plastic waveguide interconnect," *Solid-State Circuits, IEEE Journal of*, vol. 46, no. 12, pp. 3113–3125, Dec 2011.
- [3] M. Tytgat and P. Reynaert, "A plastic waveguide receiver in 40nm cmos with on-chip bondwire antenna," in *ESSCIRC (ESSCIRC), 2013 Proceedings of the*, Sept 2013, pp. 335–338.
- [4] Y. Kim, L. Nan, J. Cong, and M.-C. Chang, "High-speed mm-wave data-link based on hollow plastic cable and cmos transceiver," *Microwave and Wireless Components Letters, IEEE*, vol. 23, no. 12, pp. 674–676, Dec 2013.
- [5] B. Hualong, K. N., B. Ole, and U. Peter, "Dielectric tube waveguides with absorptive cladding for broadband, low-dispersion and low loss thz guiding," *Sci. Rep.*, vol. 5, Jan 2015.
- [6] C.-H. Lai, B. You, J.-Y. Lu, T.-A. Liu, J.-L. Peng, C.-K. Sun, and H. chun Chang, "Modal characteristics of antiresonant reflecting pipe waveguides for terahertz waveguiding," *Opt. Express*, vol. 18, no. 1, pp. 309–322, Jan 2010.
- [7] C. Yeh and F. I. Shimabukuro, *The essence of dielectric waveguides*. Springer, 2008.
- [8] W. Bruno and W. Bridges, "Powder core dielectric channel waveguide," *Microwave Theory and Techniques, IEEE Transactions on*, vol. 42, no. 8, pp. 1524–1532, Aug 1994.